

PCT No. PCT/EP00/08316
Attorney Docket: 951/50921


REMARKS

Entry of the amendments to the specification, claims and abstract before examination of the application is respectfully requested.

If there are any questions regarding this Preliminary Amendment or this application in general, a telephone call to the undersigned would be appreciated since this should expedite the prosecution of the application for all concerned.

Respectfully submitted,

March 22, 2002



Donald D. Evenson
Registration No. 26,160
Song Zhu
Registration No. 44,420

CROWELL & MORING, LLP
Intellectual Property Group
P.O. Box 14300
Washington, DC 20044-4300
Telephone No.: (202) 624-2500
Facsimile No.: (202) 628-8844
DDE:SZ:tlm
(CAM #: 80437.790)

VERSION WITH MARKINGS TO SHOW CHANGES MADE

Claims 1-9 have been amended as follows:

1. (Amended) [Display] A display device having a display unit [(10)], [which comprises] comprising a scale with graphic information [(11)] and an indicator element [(13)] which [can be] is aligned as a function of at least one input parameter with a position of the scale [(11)], [characterized in that the] wherein a display of the graphic information in an area [(B)] around [the] a momentary position of the indicator element [(13)] is emphasized in comparison [to the] with a normal display.

2. (Amended) [Display] The display device according to Claim 1, [characterized in that] wherein the area [(B) can be] is selected as a function of the input parameter [information (n, v)].

3. (Amended) [Display] The display device according to Claim 1 [or 2], [characterized in that] wherein the display of the graphic information within this area [(B) can be] is selected in a [defined] pre-determined manner.

4. (Amended) [Display] The display device according to [one of the preceding claims] Claim 3, [characterized in that] wherein the change is defined by at least one of an enlargement, a different contrast, a different color and[/or] a shift.

5. (Amended) [Display] The display device according to [one of the preceding claims] Claim 2, [characterized in that] wherein a control device [(12)]

is provided which receives the input parameter [parameters (v, n)] and is connected with the display unit [(10)].

6. (Amended) [Display] The display device according to [one of the preceding claims] Claim 1, [characterized in that] wherein a video screen display is used as the display unit [(10)].

7. (Amended) [Display] The display device according to [one of the preceding claims] claim 1, [characterized in that] wherein the display unit [(10)] is [constructed in the shape of] configured as a round instrument.

8. (Amended) [Display] The display device according to [one of the preceding claims] Claim 1, [characterized in that] wherein the graphic information is at least one of [information is] letter and[/or] number information.

9. (Amended) [Display] The display device according to [one of the preceding claims] Claim 1, [characterized in that] wherein the display unit [(10)] is] includes a speedometer of a vehicle.

MARKED Substitute Specification – PCT/EP00/08316
Attorney Docket No. 951/50921

DISPLAY DEVICE AND METHOD

BACKGROUND AND SUMMARY OF THE INVENTION

The invention relates to a display device [according to the preamble of Claim 1] and a display method.

Display devices with scales, which graphically display information, are used in all fields of technology and inform people of many different conditions of machines and equipment and about many different circumstances. A very narrow application [range] involves the vehicle [field], where vehicle operating conditions are provided to the vehicle operator by [means of] display devices. Although [the present invention] it will be described relative to this field, [this description] the present invention should not be so limited [limiting].

[More or less] How much space for the transmission of information is available depending on the local situations and the extent of the display. In the case of vehicles, for example, an increasing number of scale marks must be shown in the area of speedometer readings as a result of higher [maximal] maximum speeds. Furthermore, the available space is increasingly reduced because of additional display devices, such as the rotational speed, the tank, the navigation devices, etc. On the whole, the display units are therefore becoming smaller and are consequently more difficult to read. [In the case of] For older far-sighted persons or [at a short] with a quick glance, [problems arise with respect to the recognition] the displayed information may be difficult to

recognize. Similar problems also occur in other areas where generally little space is available for display instruments.

It is an object of the invention to further develop a display device of the [initially] above-mentioned type [in that] where the information displayed [thereby] can be absorbed rapidly and reliably.

[This object is achieved by means of the characteristics indicated in Claim 1].

A core idea of the invention is to change and emphasize the representation of the graphic information in an area [in order to change and emphasize] where the actual position of the indicator element is [with respect to the normal representation]. The type of the changes can be freely selected. In particular, it is possible to enlarge the graphic information, to [image] show it with a higher contrast, to indicate it in a different color or to displace it.

For example, normal indicator needles or graphic indicators[,] (such as marks in the scale) can be used as the indicator element.

As a result of the emphasis, a viewer is automatically directed to the area of the scale [in which] where the indicator element is situated. As a result, he can [particularly] rapidly and reliably recognize the information supplied by the indicator element.

[A] In a particularly preferred embodiment of the invention, [is characterized in that] the emphasized area [in which the emphasizing takes place] is selected as a function of input information. In particular, the size and position of the area can be changed. By changing the area, additional

information can be transmitted, for example, information concerning due movements of the indicator element.

In addition, or as an alternative, to the change of the area, the display of the graphic information in the area itself can also be changed. These changes may be predefined or be made a function of parameters. If the emphasizing is generated by enlargements of the graphic information, a decrease of the enlargement, for example, can take place with an increasing distance from the indicator element. As an alternative, a change of color or position depending on the distance of the indicator element is also possible.

A particularly advantageous embodiment can be implemented by [means of] a video screen display as an indicator unit. On the display, the graphic information can be changed in a simple manner. In contrast to a normal instrument dial indication, [in the case of a display], it is possible in a simple manner for a video screen display to show numbers or letters in an enlarged fashion, in color or displaced. The display unit, particularly the video screen display, is preferably controlled by a control device. The required parameters are fed to the control device, are processed by it and are transmitted in a processed form to the display unit.

A useful [method of] application of the invention [exists in the case] is in the area of a vehicle instrument. For example, the speedometer can be constructed in the manner described above.

The invention will be described in the following with respect to a speedometer and with respect to the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a simple schematic diagram of an embodiment of the invention[.];

Figure 2 is a representation of a speedometer whose scale is enlarged according to the invention around the indicator element; and

Figures 3a and 3b, as well as Figures 4a and 4b, are representations as shown in Figure 2[, in which case] where the areas in which the enlargements take place are changed.

DETAILED DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic view of a video screen display 10 which is connected with a control device 12. The control device 12 receives input information, [specifically in the present case, the] such as vehicle speed v and [the] rotational engine speed n .

On the video screen display 10, an indicator 13 is shown which indicates the vehicle speed v on a scale 11 (not shown in Figure 1). In addition to scaling lines, the scale 11 has number presentations which explicitly indicate the speed in km/h. [By generating] Using the scaling and the numbers on the video screen display 10, the information can be [selected] displayed in [all] different sizes and positions.

Conventionally, all information over the entire scale is indicated in a uniform size.

[In a manner according] According to the invention, as shown [indicated] in Figure 2, an area B is defined around the actual position of the indicator 13, in which the numbers are shown in an enlarged manner (compare Figure 2). [In this case, the] The size of the enlargement depends on the distance of the respective number [information] from the momentary indicator position. According to Figure 2, number 80 is shown to be the largest and number 60 is the second largest. All other numbers have the normal size. [Area] The area B is determined [in] by the control device 12 on the basis of the input parameters v and n and is [distributed] placed symmetrically around the actual indicator position.

Naturally, the emphasizing on the video screen display can also be implemented by shifts of the information, color changes or a higher contrast.

As a result of the emphasis, a driver['s glance], when briefly looking at the speedometer, is automatically directed to the enlarged area so that he can easily and rapidly detect the speed information specified more precisely by the indicator 13.

[By means of] Figures 3a, 3b, 4a and 4b[, it is illustrated] illustrate how additional information can be transmitted by the selection of the area of [the] emphasis.

In the case of acceleration[s], the area is shifted toward the higher speeds, as shown in Figure 3a [(compare Figure 3a)], so that the speeds are emphasized in an area toward which the indicator 13 is moving. In the embodiment

according to Figure 3a, the area B starts at the indicator 13 and is oriented toward the higher speeds.

Analogously, during braking operations, the area B is shifted toward lower speeds, as shown in Figure 3b [(compare Figure 3b)]. In this case, the size of the enlargement is again dependent on the distance of the number information from the actual indicator position. On the whole, in the embodiments [according to] shown in Fig 3a and 3b, the area is shifted [from its position round] around the actual indicator position depending on the driving dynamics.

However, it is not only the location of the area B that can be changed. The extent or dimension of the area B can also be adjusted. In Figures 4a and 4b, [a representation is selected, in the case of which] the size of the area of [the] emphasis depends on the extent of the acceleration. In the case of higher acceleration[s] (Figure 4a), [an emphasizing is carried out in a larger] the emphasized area B is larger than in the case of [a] less [high] acceleration ([compare] Figure 4b).

To this extent, an area of emphasis [shifted] around the actual indicator position [is a looking] looks ahead toward a future driving speed, so that an acknowledgment can be made concerning the extent of the speed change. This acknowledgment is particularly clear when scale lines are used in addition to the numbers for indicating the prediction ([compare,] see, for example, Figures 3a and 4b).

On the whole, in the case of the above-mentioned embodiments, also when a display surface is small, important information [to be indicated] can be

displayed such that it can be absorbed [also] at a brief glance. This is of special interest also for persons who do not have perfect vision.

The present invention can be used wherever a simple and rapid information transmission is important in the case of a display device. In this respect, the invention is not limited to the present embodiment.